



FOREMOST CHEMICAL TECHNOLOGIES, INC.

Lot 11 Block 10 Malakas Street, Barangay Commonwealth, Quezon City
0962 415 4137 • sales@foremostchemical.com

Tapping Compound



Kevlon™ **Tapping Compound** is a compound of base oil and additives, designed to meet the requirements for use in medium to heavy cutting operations. Its excellent lubricity promotes longer tool life, smoother finishes, and lower machining temperatures. The transparent quality of this oil provides closer observation of the work piece thereby improving accuracy and reducing errors. It does not produce any mist during operation.

Application

Tapping compound is used in a wide variety of machining operations, especially in medium and heavy tapping, cutting, and threading operations. It is also suitable for use in milling, drilling, turning and grinding, broaching, honing operations. It can be mixed with light duty cutting fluids for occasional difficult machining operations. Suitable for light to moderate machining operations of ferrous and non-ferrous material. For machining of hard to cut materials like alloy steels, high tensile steels and stainless steels. For difficult and delicate machining operations that demand very high quality finish and superior close tolerance results.

Benefits

- Provides superior surface finish
- Reduces tool wear
- Keeps work cool
- Excellent rust and corrosion protection
- Suitable for all machining operations
- Anti-wear & extreme pressure additives give longer tool life and excellent surface finish

Typical Physical Properties

Appearance

Amber or Yellowish

Odor

Mild Petroleum

Evaporation Rate

Slow

Specific Gravity @ 15°C

0.90 - 0.94

Solubility

Insoluble in Water

Form

Liquid

Available in the following packaging:

1-Liter Bottle / 4-Liter Gallon / 20-Liter Pail / 400-Liter Drum

Our engineers and representatives are always available to provide the necessary assistance to satisfy your requirements.