



FOREMOST CHEMICAL TECHNOLOGIES, INC.

Lot 11 Block 10 Malakas Street, Barangay Commonwealth, Quezon City
0962 415 4137 • sales@foremostchemical.com

Engine Oil SAE 15W40



Markem™ **Engine Oil SAE 15W40** is premium-quality commercial multi-grade oil for use in light/heavy-duty diesel and gasoline engines. It is intended primarily for the lubrication of automotive engines of commercial vehicles including those operating on relatively high sulfur diesel fuels. Markem Engine Oil 15W40 meets the requirements of modern, low emission diesel engines as well as high performance gasoline engines, allowing it to be used in mixed-fleet operations.

Application

Markem Engine Oil 15W40 multi-grade oil is designed for high-speed turbocharged or naturally-aspirated diesel and gasoline engines operating under severe service conditions occurring in commercial transport and heavy construction equipment. The oil is specially suited for mixed fleets, and its versatility enables the operator to rationalize on the number of oil grades that have to be used. Markem Engine Oil 15W40 is best for CRDI engines.

Approvals

API	CI4, CH-4, CG-4, SJ
ACEA	E3-96 Issue 3, E5-99, B3-98, A3-98, 83-98
RVI	RLD 99
Mercedes-Benz	228.1
Man	M 3275
MACK	E0-M Plus
Volvo	VDS-2
Cummins	20072, 20076, 20077

Benefits

- Markem Engine Oil 15W40, on extended field trials, have proven that the drain period can be extended beyond normal service with maximum intervals as established by regular laboratory analysis and in consultation with engine manufacturers.
- Markem Engine Oil 15W40 multi-grade oil is designed to impart excellent thermal and oxidation stability, very high detergency and dispersancy level, very good protection against corrosion and high standards of load carrying capacity. All these properties result in clean engines, both for diesel and gasoline, under either high or low temperature conditions. The compounded additive also reduce cylinder bore and piston ring wear.

Typical Physical Properties

SAE Grade SAE	Viscosity at 40 °C, cSt
15W40	112
Flash Point, °C	Viscosity at 100 °C, cSt
238	14.35
Specific Gravity at 15.6°C	Viscosity Index
0.880	133
Pour Point, °C	TBN mgKOH/g
12	9
Color, ASTM	
3.5	

Available in the following packaging:

1-Liter Bottle / 4-Liter Gallon / 20-Liter Pail / 200-Liter Drum

Our engineers and representatives are always available to provide the necessary assistance to satisfy your requirements