



## FOREMOST CHEMICAL TECHNOLOGIES, INC.

Lot 11 Block 10 Malakas Street, Barangay Commonwealth, Quezon City  
0962 415 4137 • sales@foremostchemical.com

### Hydraulic Oil 68



Markem™ **Hydraulic Oil 68** is made from high-viscosity index paraffinic base oil blended with superior anti-wear additive for use in modern high-pressure hydraulic systems. The oils are formulated to meet or exceed the performance requirements of all major hydraulic equipment manufacturers and industry organization specifications.

#### Application

Markem Hydraulic Oil 68 is a premium-quality anti-wear hydraulic fluid designed for service in mobile and stationary high-pressure hydraulic systems, as well as certain severe and sensitive applications such as in high-pressure vane pumps, coaxial pumps, and hydrostatic transmission. Also suitable for pneumatic system lubrication and can be used as high-quality circulating oil.

#### Benefits

- Excellent anti-wear performance
- Hydrolytic stability
- Excellent rust and corrosion protection
- Excellent oxidation stability
- Effective foam inhibitor prevents foam build-up in the system
- Superior filterability
- Passes wet and dry Denison T6C pump test

#### Typical Physical Properties

**SAE Grade**

68

**Physical state**

Liquid

**Color**

Yellow

**Density at 15°C, g/cc**

0.875

**Flash Point, °C**

>195

**Pour Point, °C**

-33

**Viscosity at 40 °C, cSt**

68.25

**Viscosity at 100 °C, cSt**

8.997

**Viscosity Index**

106

**Solubility**

Insoluble in water

#### Available in the following packaging:

1-Liter Bottle / 4-Liter Gallon / 20-Liter Pail / 200-Liter Drum

Our engineers and representatives are always available to provide the necessary assistance to satisfy your requirements.