



FOREMOST CHEMICAL TECHNOLOGIES, INC.

Lot 11 Block 10 Malakas Street, Barangay Commonwealth, Quezon City
0962 415 4137 · sales@foremostchemical.com

Motor Oil 40



Markem™ **Motor Oil 40** provides premium-quality service in both diesel and gasoline engines. It is specially formulated for heavy-duty service in diesel engines found in both on-highway and off-highway vehicles and equipment.

Application

Markem Motor Oil 40 is recommended as crankcase lubricant of diesel engines in automotive, industrial and heavy construction equipment, either naturally aspirated or equipped with turbochargers. When grade simplification is desired as in fleet conditions, it is also recommended for gasoline engines in passenger cars and trucks operating under engine manufacturer's maintenance procedures.

Approvals

API	CD/SF
ACEA	E1-96
MB	P.227.0
Caterpillar	T02 Friction Test
US Military	MIL-L-2104D, MIL-L-46152B
Allison	C3 / C4

Benefits

- Markem Motor Oil 40 is specially formulated with advanced dispersant technology to resist oil thickening caused by incomplete engine combustion which generates soot.
- The dispersant minimizes sludge formation and effectively keeps particles in suspension to extend filter life.
- Since it is also recommended for gasoline engines, Markem Motor Oil 40 provides mixed fleet operators the convenience of a single line motor oils for all vehicles.

Typical Physical Properties

SAE Grade	Viscosity at 100 °C, cSt
40	14.5
Specific Gravity at 15°C	Viscosity index
0.893	97
Flash Point, °C	TBN, mg KOH/g
238	9.0
Pour Point, °C	Color, ASTM
-12	3.5
Viscosity at 40 °C, cSt	
147	

Available in the following packaging:

1-Liter Bottle / 4-Liter Gallon / 20-Liter Pail / 200-Liter Drum

Our engineers and representatives are always available to provide the necessary assistance to satisfy your requirements.