



FOREMOST CHEMICAL TECHNOLOGIES, INC.

Lot 11 Block 10 Malakas Street, Barangay Commonwealth, Quezon City
0962 415 4137 · sales@foremostchemical.com

Compressor Oil ISO VG 32



Markem™ **Compressor Oil ISO VG 32** is premium quality oil made from paraffinic base oil for the lubrication of all types of air compressors. It assures the valve cleanliness in reciprocating compressors due to improved oxidation stability of the fluid and less sludge and deposit build-up as experienced with petroleum-based products.

Markem Compressor Oil ISO VG 32 has better high-temperature oxidation stability and anti-wear characteristics than other compressor lubricants, thereby extending the life of equipment and oil and decreasing the number of required oil charges.

Application

Markem Compressor Oil ISO VG 32 is suitable for use in crank cases and cylinders of stationary and screw air compressors. Also, meet certain high-performance turbine quality and hydraulic oils. Always follow the equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

Approvals

Cincinnati-Milacron	P-68, P-69, P-70
Denison	HF-2, HF-2, HF-0
AFNOR	NFE 48-603 (HM)
DIN	51506
Vickers	1-286-S3, M-2950-S
U.S Steel	126, 127

Benefits

- Minimize deposit formation
- Superior anti-wear properties
- Excellent rust and corrosion protection
- Excellent oxidation stability
- Effectively foam inhibitor prevents foam build-up in the system

Typical Physical Properties

ISO VG
32

Specific Gravity
0.855 to 0.865

Flash Point, °C
210 to 220

Viscosity @ 40°C
30 to 35

Viscosity @ 100°C
5.0 to 6.0

Viscosity Index
87 to 117